




PJ2W

Performance and Technical Data

PERFORMANCE DATA



FUEL CONSUMPTION SUBJECT TO 5% VARIANCE IN ACCORDANCE WITH ISO 14364:2004 & ISO/IEC 15926-1:2004

Operating at this speed, torque & power is limited to 1500 RPM continuous.

Generator T class is designed for normal duty use. For special applications, consult your local John Deere distributor.

Generator T class is not for power generation.

Generator T class is not for use in applications requiring a specific speed.

The above data are approximate and are based on ISO 14364:2004 & ISO/IEC 15926-1:2004. Actual performance may vary due to operating conditions, altitude, ambient temperature, etc.

John Deere
Generator T class
1500 RPM CONTINUOUS RATING
1700 RPM 1 HOUR RATING
1900 RPM VARIABLE SPEED RATING

Rated Power (kW/HP)	1500	1700	1900	2000
Maximum Torque (kgm/kN)	14	16.7	19.2	20.2
Max Torque (kgm/kN) @ 1500 RPM	12	14.7	16.8	17.8
Rated Torque (kgm/kN)	12.5	14.7	16.8	17.8
Rated Power (kW/HP)	24.0	28.0	32.0	34.0
1. Maximum Torque (kgm/kN)	16.7	19.2	20.2	21.2
2. Maximum Torque (kgm/kN)	16.7	19.2	20.2	21.2
3. Maximum Torque (kgm/kN)	16.7	19.2	20.2	21.2
4. Torque (kgm/kN)	16.7	19.2	20.2	21.2

